

Planter Box Hinges

INSTALLATION INSTRUCTIONS

PLEASE READ THE ENTIRE INSTRUCTION SHEET BEFORE STARTING INSTALLATION.

Please refer to the manufacturer's operator's manual for pertinent safety precautions. **THINK SAFETY. WEAR SAFETY GLASSES.**



1. With the lid securely attached, hold the QuickHinge up to the planter box. Position the hinge in the center of the box. Be sure that the bottom edge of the top bracket is flush with the bottom edge of the lid and that the bottom bracket is touching the bottom of the lid. While holding the QuickHinge in this position, take a marker and mark all four holes. (as shown in photo A)
2. **IMPORTANT! First remove the lid from the box.** Then, using a 5/16 inch drill bit, drill the holes in the lid. Next, drill the holes in the box. When drilling the holes in the box, cheat the drillbit down 1/8" - 1/4" from the center of the marking. This will insure a snug fit when the lid is closed. (as shown in photo B, & C,)
3. Bolt the brackets to the box and lid with the included hardware. Be sure to put the flange nuts on the inside of both the lid and the box. Then with a 1/2" wrench, tighten all of the bolts. (as shown in photo D, & E,)
4. Re-attach the lid to the box. With the two brackets now lined up, put the pin through the bracket and insert the spring clip into the pin. (as shown in photo F)

WARNING Proper application, installation, and operation of any machine and/or installation incorporating products sold by May Wes Manufacturing is the responsibility of the purchaser and/or end user. All local, state, and federal safety codes must be followed. May Wes Manufacturing is specifically not responsible for property damage and/or personal injury, direct or indirect, for damages and/or failures caused by improper design, application, installation, operation, abuse, and/or misuse of its' products.

Visit us online at www.maywes.com to see other innovative products!